



REVISION INFORMATION			
Rev.	Rev. Date	Modified By	Brief Description
A/0	2017.09.21	LM	NEW



INK MARKING: FTP CAT.5E 350MHZ PATCH ISO/IEC 11801 & EN 50288 3P CONFORMS FOR GIGABIT ETHERNET ▲ 26AWGX4P
 TYPE CMX(UL) C(UL) CMH E164469-XX

Jacket Color
BK012
BU608
GN509
GY177
OR307
RD210
RD220
PU720
WH928
YE406



orange 1	green 2
white/orange	white/green
blue 3	brown 4
white/blue	white/brown

PINOUT		SHIELD	
P1	WIRE	P2	SHIELD
1	WHITE/ORANGE	1	
2	ORANGE	2	
3	WHITE/GREEN	3	
6	GREEN	6	
5	WHITE/BLUE	5	
4	BLUE	4	
7	WHITE/BROWN	7	
8	BROWN	8	
	SHIELD		SHIELD
	DRAIN		

conductor resistance: 152 Ω /Km at 20°C

L(ft)	T(inch)	T(%)	L(ft)	T(inch)	T(%)
0.5	±0.6	10%	15	±3.15	1.75%
1	±1.2	10%	20	±4	1.67%
1.5	±1.2	6.67%	25	±4	1.33%
2	±1.2	5%	35	±6	1.43%
3	±1.2	3.33%	50	±6	1.0%
4	±1.2	2.5%	75	±6	0.67%
5	±1.2	2%	100	±6	0.5%
6	±1.2	1.67%	125	±6	0.4%
7	±2	2.38%	150	±6	0.33%
10	±2	1.67%	175	±6	0.29%
			200	±6	0.25%

③	MOLD	PVC YUS-07	2	PCS
②	PLUG	8P8C 50U RJ45 SHIELDED	2	PCS
①	CABLE	CAT.5E FTP PVC 26AWG*4P BC	1	PC
NO.	PART NAME	SPECIFICATION DESCRIPTION	QTY	UNIT

CAT 5E SHIELDED PATCH CABLES.