



Features & Specification:

- 1.Low Insertion Loss: $\leq 0.3\text{dB}$
- 2.Pre-radiused, UPC-end finish for physical contact: $R10$ to 25mm
- 3.Repeatability(500 mating cycles): $\leq 0.2\text{dB}$
- 4.Tensile Strength: $\geq 5\text{KG}$
- 5.Exchangeability: $\leq 0.2\text{dB}$
- 6.Operation Temperature: -20°C to $+70^{\circ}\text{C}$
- 7.Storage Temperture: -40°C to $+70^{\circ}\text{C}$
- 8.RoHS Compliant.
- 9.Standard product made on 2mm and PVC jacket(Also available for LSZH & plenum jacket).
- 10.Meet all international reliability standards.

4	Shrink Tube (RoHS Compliant)	2
3	Cable Marker (RoHS Compliant)	4
2	Fiber Cable: 50/125 μm , OD 2mm Jacket Color: Orange(RoHS Compliant)	1
1	Connector Type: LC MM/UPC Duplex / LC MM/UPC Duplex	2SETS
NO	DESCRIPTION	Q' TY

Datacomm Cables Inc.	CUSTOMER:	
	PART NO:	
DRAW:	TITLE: MM 50/125 Duplex LC-LC	
CHECKED:	DRAW NO.:	REV.
APPROVED:		UNIT: mm SCALE: 1:1 SHEET: 1/1