



XX (M) + 10 / -0

Features & Specification:

1. Low Insertion Loss: $\leq 0.3\text{dB}$
2. Used in 10Gb ethernet & fast ethernet and FDDI networks.
3. 850nm VCSEL based GbE(1000 base-SX) to support longer distance.
4. Pre-radiused, UPC-end finish for physical contact: R10 to 25mm
5. Repeatability(500 mating cycles): $\leq 0.2\text{dB}$
6. Tensile Strength: $\cong 5\text{KG}$
7. Exchangeability: $\leq 0.2\text{dB}$
8. Operation Temperature: -20°C to $+70^\circ\text{C}$
9. Storage Temperature: -40°C to $+70^\circ\text{C}$
10. RoHS Compliant.
11. Standard Product made on 2mm PVC jacket (Also available for LSZH & Plenum jacket)
12. Meet all international reliability standards.

4	Shrink Tube (RoHS Compliant)	2
3	Cable Marker (RoHS Compliant)	4
2	Fiber Cable: OM5 Duplex 2.0 Lime Green	1
1	Connector Type: LC/LC Duplex MM (RoHS Compliant)	2SETS
NO	DESCRIPTION	Q' TY

CUSTOMER:	
PART NO.:	
TITLE: OM5 Duplex 2.0 LC-LC	
DRAW NO.:	
UNIT	mm
SCALE	1:1
REV.	A
SHEET	1/1